

## Standards

### [RFS21 - Specification for Radio Apparatus: VHF Land Mobile Service](#)

Using Amplitude Modulation with 12.5kHz Carrier Frequency Separation

### [RFS27 - Specification for Radio Apparatus: Telecommand and Telemetry](#)

Specification for Radio Apparatus: Telecommand - For the transmission of signals to initiate, modify or terminate functions of equipment at a distance. Telemetry - For automatically indicating or recording measurements at a distance from the measuring instrument.

### [RFS32 - Specification for Radio Apparatus: UHF Trunked Dispatch Service Using Angle Modulation with 25kHz Carrier Frequency Separation and a Maximum Deviation of \$\pm 5\$ kHz](#)

UHF Trunked Dispatch Service Using Angle Modulation with 25kHz Carrier Frequency Separation and a Maximum Deviation of  $\pm 5$ kHz

### [RFS36 - Specification for Radio Apparatus: VHF and UHF Fixed Services Using Angle Modulation with 25kHz or 50kHz Carrier Frequency Separation](#)

VHF and UHF Fixed Services Using Angle Modulation with 25kHz or 50kHz Carrier Frequency Separation

### [RFS37 - Radio Linking System: Studio to Transmitter Linking System Using Angle Modulation with Carrier Frequency Separation between 75 and 500kHz](#)

Studio to Transmitter Linking System Using Angle Modulation with Carrier Frequency Separation between 75 and 500kHz

### [Archived standards](#)

This folder contains standards that no longer apply and that may be superseded by other documents.